Registered office:

Caleb Components Limited Block 6 Grazebrook Industrial Park Peartree Lane, Dudley West Midlands DY2 0XW England

Tel: 0044 (0)1384 453955 **Fax:** 0044 (0)1384 257423

Email: sales@calebcomponents.com
Buy Online: www.springfasteners.co.uk



Split Cotter Pins

Here at Caleb Components, we are stockists of high quality Split Cotter Pins.

Split Cotter Pins are a simple securing device for example, to prevent parts sliding off the end of a shaft. The prongs (or legs) of the Cotter Pins can then be bent back to hold the assembly in place.

The standard specification or standard for Cotter Pins is DIN 94, equivalent to ISO 1234 and BS 1574

Our standard Cotter Pin range are produced in Mild Steel, with a Bright Zinc Plate finish.

We can also offer in materials such as:

- 316 (A4) Stainless Steel
- Phosphor Bronze
- Brass

Our metric range covers nominal diameters from 1.6mm to 13.0mm Our imperial range covers nominal diameters from 1/16" to 1/2"

To view our standard range of metric and imperial Split Cotter Pins, please see the pages below.

Split Cotter Pins

The standard sizes for metric Split Cotter Pins (DIN 94)

** Please note! The length of a Cotter Pin is measured from beneath the head of the Cotter Pin to end of the shortest leg**

			Ottor i ii			1	9	ı		
Nominal										
Diameter	1.6mm	2.0mm	2.5mm	3.2mm	4.0mm	5.0mm	6.0mm	8.0mm	10.0mm	13.0mm
Length										
10mm	Υ	Υ								
12mm	Υ	Υ	Υ							
14mm	Υ	Υ	Υ	Υ						
16mm	Υ	Υ	Y	Y						
18mm	Υ	Υ	Υ	Υ						
20mm	Υ	Υ	Y	Y	Υ					
22mm	Υ	Υ	Υ	Υ	Υ	Υ				
25mm	Υ	Υ	Y	Y	Υ	Υ				
28mm	Υ	Y	Υ	Υ	Υ	Y				
32mm	Υ	Υ	Υ	Υ	Υ	Υ	Υ			
36mm	Υ	Υ	Υ	Υ	Υ	Υ	Υ	Υ		
40mm	Υ	Υ	Υ	Y	Υ	Υ	Υ	Υ		
45mm			Υ	Y	Υ	Υ	Υ	Υ		
50mm		Υ	Y	Y	Υ	Υ	Υ	Υ	Υ	Υ
56mm				Υ	Υ	Υ	Υ	Υ	Υ	Υ
63mm				Υ	Υ	Υ	Υ	Υ	Υ	Υ
71mm					Υ	Υ	Υ	Υ	Υ	Υ
80mm					Υ	Υ	Υ	Y	Y	Υ
90mm						Υ	Υ	Υ	Υ	Υ
100mm						Υ	Υ	Y	Y	Υ
112mm						Υ	Υ	Υ	Υ	Υ
125mm							Υ	Y	Y	Υ
140mm									Y	Υ
160mm									Υ	Υ

Split Cotter Pins

The standard sizes for imperial Split Cotter Pins

** Please note! The length of a Cotter Pin is measured from beneath the head of the Cotter Pin to end of the shortest leg**

			JOHET EII	i to cito	or tile 3	11011031	- S			1
Nominal Diameter	1/16"	5/64"	3/32"	1/8"	5/32"	3/16"	1/4"	5/16"	3/8"	1/2"
Diameter	1/10	3/04	3/32	1/0	3/32	3/10	1/-	3/10	3/0	1/2
Length										
3/8"	Υ	Υ								
1/2"	Υ	Υ	Υ							
5/8"	Υ	Υ	Υ	Υ						
3/4"	Υ	Υ	Υ	Υ	Υ					
7/8"	Υ	Υ	Υ	Υ	Y	Υ				
1.00"	Υ	Υ	Υ	Υ	Υ	Υ				
1.1/8"	Υ	Y	Υ	Υ	Υ	Υ				
1.1/4"	Υ	Y	Υ	Υ	Υ	Υ	Υ			
1.1/2"	Υ	Y	Υ	Υ	Y	Υ	Υ	Υ		
1.3/4"			Υ	Υ	Υ	Υ	Υ	Υ		
2.00"			Υ	Υ	Y	Υ	Υ	Υ	Υ	
2.1/4"				Υ	Y	Υ	Υ	Υ	Υ	
2.1/2"				Υ	Y	Υ	Υ	Υ	Υ	
2.3/4"					Y	Υ	Υ	Υ	Υ	
3.00"					Y	Υ	Υ	Υ	Υ	Υ
3.1/2"						Υ	Υ	Υ	Υ	Y
4.00"						Υ	Υ	Υ	Υ	Y
4.1/2"						Υ	Υ	Υ	Υ	
5.00"							Υ	Υ	Υ	Υ
5.1/2"									Υ	
6.1/4"									Υ	Y

Tel: + 44 (0) 1384 453955 - **Fax:** + 44 (0) 1384 257423 - **E-mail:** sales@calebcomponents.com